

Technical Parameters - Indoor Series

Specification	P1.25	P1.5	P1.6	P1.8	P2.0	P2.5	P3	P4
Pixel Pitch (mm)	1.25 mm	1.5 mm	1.6 mm	1.8 mm	2.0 mm	2.5 mm	3.0 mm	4.0 mm
Pixel Density (Pixels/sqm)	640000	426409	362404	281961	250000	160000	111111	62500
Cabinet Size (mm)	480 (W) x480 (H)/640 (W) x360 (H)/960 (W) x960 (H)							
Redundancy Power & Data	Yes (Optional)							
Pixel Calibration	Standard color and brightness calibration							
Brightness (cd/m2)	≤ 1200							
Grey Scale	12 ~ 16Bit							
Color Temperature	3000 ~ 10000 Adjustable							
Drive Mode	Constant Current Drive							
Frame Frequency	50/60Hz							
Refresh Rate	Standard Refresh: ≤ 1920; High Refresh Rate: ≤ 3840							
Working Voltage	AC: 110V ~ 240V, 50/60Hz							
Power Consumption	500W							
Lifetime (hours)	≤ 100000h							
Operating Temp. (°C)	- 10 °C ~ 60 °C							
Storage Temp. (°C)	- 20 °C ~ 60 °C							
Humidity Range	10% ~ 90%, Non condensing							
Ingress Protection	IP43							
Weight	6.2 kgs/6.7 kgs/32 kgs							
Working Enviroment	Indoor							

Classical Cases



Command & Control Room



Conference Room



Train Tracking System

Imperial Techsol Private Limited

Address: B-4, BPL Tower, Kh. No. 405, MG Road, Ghitorni, Delhi - 110030

Web: www.imperialtechsol.com Email: marketing@imperialtechsol.com

NYSYSTM
PERFORMANCE MATTER



Indoor LED Video Wall