

LightStream® WXGA 1280x800 Projector with 4,000 Lumens

True-to-Life Color + Smart Design

PJD7526W



Perfect for classrooms or meeting rooms with high ambient light, the ViewSonic® LightStream® PJD7526W projector delivers presentations that always shine bright. Thanks to SuperColor™ technology and the brilliance of 4,000 lumens, this projector strikes a perfect balance of color and light to deliver amazing brightness and front-of-screen performance. Whether the shades are drawn, or the room is fully lit, lesson plans, presentations, and multimedia content are brought to life. A smart and intuitive design includes PortAll™—a hidden MHL/HDMI port perfect for wireless dongles (such as the optional ViewSonic WPG-300) that lets you wirelessly stream multimedia content from a mobile device, or notebook PC, to the projector. Designed with an easy-to-use network management system that lets you remotely control over 250 LightStream projectors, the PJD7526W is great for use in multiple classrooms across an entire campus, or multiple meeting rooms in an office building.

Key Features:

- Best in class color accuracy
- 4,000 lumen high brightness
- Secure MHL/HDMI port
- Network capable
- Smart design

Designed for:

- Education
- Business

LightStream XGA 1024x768 Projector with 4,000 Lumens

PJD7526W

Projection Distance		Screen Size (16:10) Diagonal	
Inches	Meters	Inches	Meters
39-43	1.0-1.1	30	0.8
53-58	1.3-1.5	40	1.0
49-87	2.0-2.2	60	1.5
105-115	2.7-2.9	80	2.0
131-144	3.3-3.7	100	2.5
197-216	5.0-5.5	150	3.8
263-288	6.7-7.3	200	5.1
329-360	8.4-9.2	250	6.4
394-432	10.0-11.0	300	7.6



Specifications

DISPLAY	Type	0.65" Digital Micromirror Device (DLP™)
	Resolution	1280 x 800 (native)
	Lens	1.1x manual optical zoom / manual optical focus
	Keystone	Vertical (± 30°)
	Size	30 – 300 in. / 0.76 – 7.62 m (diagonal)
	Throw Distance	3.3 – 36.0 ft. / 1.0 – 10.98 m
	Throw Ratio	1.55~1.7:1
	Lamp	240 watt
	Light Life	3500 / 6500* (Normal / Eco-mode)
	Brightness	4000 lm
	Contrast Ratio	22,000:1 (DynamicEco mode)
	Aspect Ratio	16:10 (native)
Color Depth	30 bits, 1.07B Color (10+10+10)	
INPUT SIGNAL	Computer and Video	NTSC M(3.58MHz), 4.43MHz, PAL (B, D, G, H, I, M, N, 60), SECAM (B, D, G, L, L1), SD 480i and 576i, ED 480p and 576p, HD 720p, 1080i, 1080p
	Frequency	Fh: 15–100KHz, Fv: 24–120Hz
COMPATIBILITY	PC	Up to 1920x1080
	Mac®	Up to 1920x1080 (may require MAC adapter)
CONNECTOR	Digital Input	HDMI 1.4 (x1) / HDMI/MHL (x1)
	RGB Input	15-pin mini D-Sub (x2)
	Composite Input	RCA jack (x1)
	Audio In	3.5mm mini jack (x2)
	Audio Out	3.5mm mini jack (x1)
	Video Out	15-pin mini D-Sub (x1)
	USB	Mini type B (mouse control and maintenance)
	Control	RS232
Network	RJ45	

AUDIO	Speaker	10W (x1)
NOISE LEVEL	Normal / Eco-mode	36 dB / 31 dB
POWER	Voltage	100~240VAC (Auto Switching), 50-60Hz (universal)
	Consumption	350W (max) / <0.5W (stand-by mode)
CONTROLS	Basic	Power, keystone/arrow keys, left/blank, menu/exit, right/panel key lock, mode/enter, auto, source
	OSD	Display, Picture, Source, System Setup (Basic), System Setup (Advanced), Information (See user guide for full OSD functionality)
OPERATING CONDITIONS	Temperature	32–104° F (0–40° C)
	Humidity	0–90% (non-condensing)
	Altitude	0–6000 ft (1828.8m)
DIMENSIONS (W x H x D)	Physical	12.44 x 8.98 x 4.08 in. / 316 x 228 x 103.7 mm
	Packaging	16.14 x 8.86 x 17.72 in. / 410 x 225 x 450 mm
WEIGHT	Net	5.5 lb. / 2.5 kg
	Gross	9.3 lb. / 4.2 kg
REGULATIONS	Mexico Energy test/Registration, TUV-S Mark (Argentina, India BIS, FCC, CE EMC, CB, CCC, RoHS, REACH, SVHC, WEEE, ErP, cTUVus, Mexico NOM, KC, PSB, CECP, RCM	
WARRANTY	3-year limited warranty on parts and labor, 1-year limited warranty on lamp, 1st year free Express Exchange® service**	

Optional Accessories (Sold Separately)

Wireless Presentation Gateway	ViewSync3
Wireless Presentation Gateway Dongle.....	WPG-300
3D Active Shutter Glasses.....	PGD-350
Universal Ceiling Mount.....	PJ-WMK-006
Carrying Case.....	PJ-CASE-008
Replacement Lamp	RLC-105

What's in the box?

PJD7526W projector, power cable, VGA cable, remote control (batteries included), Quick Start Guide, ViewSonic Wizard CD (with User Guide)



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by TUV NORD.